



GLOBAL BATT

Energize the World



DRY CHARGED BATTERY



HIGH PERFORMANCE

LONG LIFE



AUTOMOTIVE

BATTERY

GLOBAL BATT- Dry Charge Automotive Battery Series uses a proven technology combined with the latest battery designs that have provided higher performance than previously achieved.

This battery series offers an optimal combination of price and performance and is the obvious choice for customers who demand an excellent product for a super price. In this respect, this battery series is the ideal solution - reliable power for the pure engine start, limited maintenance by means of proven lead-calcium with low antimony technology. And due to these batteries are shipped under dry charged and unfilled state without acid inside, that's led the maximum power freshness could be ensure and low self discharge rate also long storage time could be happen, and the highest transport safety standards.

S.no	Model Name (OID JIS)	Model Name (New JIS)	Capacity	No Of Plates	Dimension (±0.3mm)				Weight (Kg.)
					L	W	H	TH	
1	NS40	32B20R	32AH	8	197	129	203	227	6.9
2	NS40Z	32B20R	35AH	9	197	129	203	227	7.3
3	NS60A	40B24R/L	40AH	9	238	129	203	227	7.8
4	NS60	46B24	45AH	11	238	129	203	227	8.75
5	N50	48D26R/L	50AH	9	260	173	204	225	9.25
6	N50Z	55D26R/L	60AH	11	260	173	204	225	10.55
7	NS70	65D26R/L	65AH	13	260	173	204	225	12
8	NX110-5	80D26R/L	70AH	15	260	173	204	225	15
9	N70	65D31R/L	70AH	13	306	173	204	225	12
10	N 70Z	75D31R/L	75AH	15	306	173	204	225	15
11	NX120-7	95D31R/L	80AH	15	306	173	204	225	15
12	N100A	95E41R/L	88AH	15	410	176	213	234	15
13	N100	95E41R/L	95AH	17	410	176	213	234	15.5
14	N120	105F51	110AH	19	513	182	213	248	19.3
15	N120F	115F51	120AH	21	513	182	213	248	20
16	N150	135G51	135AH	23	510	225	212	248	21
17	N150F	145G51	150AH	25	510	225	212	248	22.5
18	N200	165H52	200AH	29	520	278	220	248	28
19	N200 L	190H52	200AH	31	520	278	220	248	29

Feature :

- Proven technology delivers reliable power.
- Lead-Calcium low antimony alloy for better anti-crossion and reduce the water consuming, effectively reduce the regular maintenance rate.
- The latest in polyethylene envelope with glass fiber separator to protect against vibration.
- Polypropylene case and cover resists damage from gasoline and oil, withstands extreme weather conditions.
- Optimized internal construction for high cranking power.
- Extremely low self discharge rate.
- Shipped and unfilled with acid gives the product a long shelf life up to 24 months.
- Cost effective.



A2D ENERGY GLOBAL LLP
#570, BAKOLI, NEW DELHI-110036, INDIA

+91-8800087673/+91-9811116847
deepak@globalbatt.in
www.globalbatt.in